



| Туре | |
|-------------|--|
| Project | |
| Catalog No. | |



DESCRIPTION

CH-FX-41-FR

Fixture channel with or without frosted lens. Great for architectural applications. Anodized aluminum finish channel with optional metal endcaps for a high end finshed look. Optional snap-on frosted lens cover completely diffuses JESCO's, patent pending, INFINA AC LED flex strip. For Hardwiring applications only.

FEATURES

- Even light distribution ٠
- Minimal glare and hotspots •
- Metal endcaps ٠

- APPLICATIONS Showcase ٠
- Display •
- Exhibition ٠
- Accent Task
- LUMEN DATA WITH INFINA IN CH-FX-41-FR

| Length | Watts | Color Temp | Lens | Lumens* | Efficacy |
|--------|-------|------------|-----------------|---------|----------|
| | 4.95 | 2700K | FROSTED (FR) | 288 | 58.2 |
| 12in. | | 3000K | | 300 | 60.6 |
| | | 4000K | (110) | 333 | 67.3 |

*lumen data based on light transmittance of frosted lens and INFINA's published lumen data.

CHANNEL OPTIONS

| MODEL | EL DESCRIPTION | |
|----------------------------|---|--|
| CH-FX-41-FR | Channel Set- Anodized aluminum channel with frosted lens cover Dims: 1-3/4"H x 1-3/8"W x 78-3/4"L | |
| CH-FX-41 | Channel only- Anodized aluminum channel Dims: 7/8"H x 1-3/8"W x 78-3/4"L | |
| CHANNEL SET ACCESSORIES | | |
| MODEL | DESCRIPTION | |
| CH-FX-41-LEC | Live Endcap | |

CH-FX-41-DEC Dead Endcap





www.jescolighting.com support@jescolighting.com Tech Support: 855.592.0029

15 Harbor Park Drive Port Washington, NY 11050 Main Line: 800.527.7796 Fax Line: 855.265.5768

219 South 6th Ave City of Industry, CA 91746 Main Line: 855.654.0110 Fax Line: 626.333.2955

7/25/2016

SPECIFICATIONS

| Length | 78-3/4 inch |
|---------------------|---|
| Light Transmittance | 60% |
| Lens Type | Frosted Polycarbonate |
| Beam Angle | 140° |
| Mounting | Surface Mount by Screws For hardwiring installations only |
| Environment | Indoor-Dry Channel & Frosted Lens Outdoor-Wet Channel Only |

| AC Flex Strip Mounting | 3M VHB 4905 Double-Sided Tape ¾ in. wide included | |
|------------------------|--|--|
| Warranty | 5 Years – see published warranty terms for detailed information. | |